

ZigBee-Based Home Automation System

Jasvivek Singh Reehal, Sukhwinder Singh

Abstract— In recent years, the home environment has seen a rapid introduction of digital and network technology. This technology offers exciting opportunities to increase the connectivity of devices within a house for the purpose of home automation. With the rapid expansion of the Internet, there is the added potential for the remote control and monitoring of such network enabled devices. But, the adoption of home automation systems has been slow. This paper identifies the reasons for this slow adoption and evaluates the potential of ZigBee for addressing these problems through the design and implementation of flexible home automation architecture. A ZigBee based home automation system and Wi-Fi network are integrated through a common home gateway. The home gateway provides network interoperability, a simple and flexible user interface, and remote access to the system. A dedicated virtual home is implemented to cater for the system's security and safety needs. To demonstrate the feasibility and effectiveness of the proposed system, four devices, a light switch, radiator valve, safety sensor and ZigBee remote control have been developed and evaluated with the home automation system.

Index Terms— Home Automation, ZigBee, Sensor Network, Network Architecture.

I. INTRODUCTION

In recent years the introduction of network enabled devices into the home environment has proceeded at an unprecedented rate. Also, with the rapid expansion of the Internet, there is the potential for the remote control and monitoring of such network enabled devices. But, the new and exciting opportunities to increase the connectivity of devices within the home for the purpose of home automation remain largely unexploited.

A. Existing Home Automation Technologies

There are many definitions of home automation available in the literature. [1] describes home automation as the introduction of technology within the home to enhance the quality of life of its occupants, through the provision of different services such as tele-health, multimedia entertainment and energy conservation. There has been significant research into the field of home automation. The X10 industry standard, developed in 1975 for communication between electronic devices, is the oldest standard identified from the author's review, providing

limited control over household devices through the home's power lines. Recently, research into the field of home automation has continued to receive much attention in academia. [2] developed a Java based automation system. An embedded board physically connected all the home automation devices and, through integration with a personal computer based web server, provided remote access to the system. The use of Java technology, which incorporates built-in network security features, produces a secure solution. But, the system requires an intrusive and expensive wired installation and the use of a high end PC. [3] introduced a Bluetooth based automation system, consisting of a primary controller and a number of Bluetooth sub-controllers. Each home device is physically connected to a local Bluetooth sub-controller. The home devices communicate with their respective sub-controller using wired communications. From the sub-controller all communications are sent to the primary controller using wireless communications. It is desirable for each home device to have a dedicated Bluetooth module. But, due to the fiscal expense of Bluetooth technology, a single module is shared amongst several devices. This architecture reduces the amount of physical wiring required and hence the intrusiveness of the installation, through the use of wireless technology. But, the architecture does not completely alleviate the intrusiveness of the installation due to the incorporation of some wired communications. Also the sharing of a single Bluetooth module between many devices has the disadvantage of incurring an access delay. [4] introduced a phone based remote controller for home and office automation. The system differs in that all communications occur over a fixed telephone line and not over the Internet. The system can be accessed using any telephone that supports dual tone multiple frequency (DTMF). The disadvantages of this system are threefold: users are not provided with a graphical user interface, users have to remember an access code, and they have to remember which buttons to press for the control of connected devices. [5] proposed a novel control network, using hand gestures. The controller uses a glove to relay hand gestures to the system. The problem with the system lies in the inaccuracy of hand gestures, with the potential for normal arm movements being inaccurately interpreted as commands. Also, there is the risk of user fatigue if repetitive hand gestures are required. The introduction provides a short review of the existing academic research into home automation. The publically available research into home automation lies predominantly in the academic arena, with little industrial research being publically available. The adoption of home automation technologies into commercial systems has been limited, and where available consumer uptake has been slow. The aforementioned systems offer little in the way of interoperability. Attempts have been made to provide network interoperability and remote access to home automation systems through the development of home

Manuscript received March 20, 2014

Jasvivek Singh Reehal, Student, Electronics, PEC University of Technology, Chandigarh, India

Sukhwinder Singh, Mentor, Electronics, PEC University of Technology, Chandigarh, India

gateways. [6] defined a home gateway as the point of ingress between a personal area network and a public access network. They developed a web server based home gateway to interconnect IEEE1394, with a power line based home automation system, and the Internet. To make the system more attractive to home owners, a real time AV transcoding capability was included. The system offers an insightful look into the development of a home gateway; But, the use of power lines as the communication medium limits the positioning of devices within the home to areas in close proximity to power sockets. [7] proposed a home energy management focused home gateway, which connects the home network with the Internet. The system was installed in twenty houses in the Tokyo area. [8] proposed a home gateway based on the OSGI (Open Service Gateway Initiative), which allows service providers to access home automation systems for administration and maintenance services. The proposed system is divided into two subsystems. The first is the DSM (Digital Home Service Distribution and Management System), which provides a user interface for the control and monitoring of connected home automation devices. The second is the Home Gateway, which is responsible for managing the home automation system. This open architecture raises privacy problems which, for some users, may be much greater than the advantages offered by granting third party access. [9] implements a home gateway that accepts mobile phone signals and activates or deactivates a LED representing a home device. These systems have made a significant contribution to the development of a home gateway. But, the existing network infrastructure within the home environment has not been taken into consideration when selecting the networks for integration with the respective home gateways. Also, the existing research has focused on the provision of remote connectivity and has largely neglected investigating the integration of existing local networks.

B. Analysis of the Existing Systems The adoption of home automation technology by consumers has been limited. We propose that, from the home automation domain analysis, the problems limiting wide spread consumer adoption can be grouped into five general categories. Firstly, complex and expensive architecture: the existing systems architectures generally incorporate a personal computer for the purposes of network management and provision of remote access. This adds additional complexity to the system, hence increasing the overall fiscal expense. Secondly, intrusive installation: the majority of systems require varying levels of physical wiring in their architectures. This, in some cases, is due to the expense of the alternative wireless technologies. Hence, these systems require intrusive and expensive installations. Thirdly, lack of network interoperability: both home networks and the home automation systems which utilise them have been developed and adopted in an unplanned and ad-hoc manner. This has lead to a home environment consisting of a complex maze of heterogeneous networks. These networks and the systems that utilise them normally offer little interoperability; leading to three potential problems: duplication of monitoring activities, due to lack of interoperability, the possibility of interference, between co-existing networks and the potential for two simultaneous, autonomous actions on co-existing

networks, interacting and resulting in an undesirable outcome.

Fourthly, interface inflexibility: the existing systems offer varying approaches for users to control and monitor the connected devices. But, this is normally limited to a single method of control, which offers users limited flexibility. The systems which provide more than one interface device normally provide different user interfaces and risk confusing users. Finally, security and safety: the existing approaches have not focused on security and safety problems that may arise from their implementation. Also, the systems that offer some degree of security have neglected the problems with sharing information between devices produced by multiple vendors for the purposes of establishing security.

B. Features of the proposed System

This paper presents a novel, stand alone, low-cost and flexible ZigBee based home automation system. The architecture is designed to reduce the system's complexity and lower fiscal costs. Hence, the system endeavours not to incorporate complex and expensive components, such as a high end personal computer, where possible. The system is flexible and scalable, allowing additional home appliances designed by multiple vendors, to be securely and safely added to the home network with the minimum amount of effort. The system allows home owners to monitor and control connected devices in the home, through a variety of controls, including a ZigBee based remote control, and any Wi-Fi enabled device which supports Java. Additionally, users may remotely monitor and control their home devices using any Internet enabled device with Java support. A home gateway is implemented to facilitate interoperability between heterogeneous networks and provide a consistent interface, regardless of the accessing device. A virtual home pre-processes all communications before they are realised on the real home automation system. All communications are checked for security and safety before being allowed to continue to their respective destinations. This paper is organised as follows: Section 2 discusses the developed home automation architecture, including a review of the technology used. Section 3 describes the implementation of the proposed system. Section 4 provides a discussion of the system evaluation and Section 5 provides a conclusion.

II. SYSTEM ARCHITECTURE

This section describes the conceptual design of a flexible and low cost home automation infrastructure. The home's low data rate, control and monitoring needs are catered for using Zigbee. The home's high data rate needs, such as multimedia applications, are met by the Wi-Fi (IEEE 802.11g) standard. A home gateway is implemented to provide interoperability between the heterogeneous Zigbee and Wi-Fi networks, and facilitate local and remote control and monitoring over the home's devices. A virtual home is implemented for the provision of real time security and safety for the home and its inhabitants. The proposed system consists primarily of four

steps. Remote user can access the system using the Internet. The remote user's communications traverse the internet until they reach the home network. They are then wirelessly transmitted to the Home Gateway using the homes Wi-Fi network. The Home Gateway is integrated with a virtual home. These communications are checked and processed by the home gateway and virtual home, as discussed in greater detail later. This checking process involves communication with the home networks coordinator, which is integrated with the home's device database and contains the status of all connected devices. Once checked the communications are sent to the real home automation system and the respective device. Additionally, a local ZigBee based remote control can be used to directly control connected devices.

A. Residential Networks

As discussed, the proposed system architecture implements a ZigBee based home automation network and a Wi-Fi based multimedia network. Alternative standards could have been integrated with the home gateway. But, the use of Zigbee and Wi-Fi offers certain advantages. Zigbee technology is designed to be used on applications that require low data rate, low-cost, low power consumption, and two way wireless communications. The Wi-Fi standard is designed to provide relatively high data rate communications. Wi-Fi has the advantage of an existing and wide spread presence in homes in the United Kingdom. The combination of Zigbee and Wi-Fi technologies has the potential to provide a comprehensive home automation solution.

B. Zigbee technology

ZigBee is a radio frequency (RF) communications standard based on IEEE 802.15.4. The Zigbee coordinator is responsible for creating and maintaining the network. Each electronic device (i.e. Washing Machine, Television, Lamp etc) in the system is a Zigbee device managed by the coordinator. All communication between devices propagates through the coordinator to the destination device. The wireless nature of ZigBee helps overcome the intrusive installation problem with the existing home automation systems identified earlier. The ZigBee standard theoretically provides 250kbps data rate, and as 40kbps can meet the requirements of most control systems, it is sufficient for controlling most home automation devices. The low installation and running cost offered by ZigBee helps tackle the expensive and complex architecture problems with existing home automation systems, as identified earlier.

C. Wi-Fi Technology

In the proposed system architecture, Wi-Fi is used for two primary purposes. Firstly, it is the chosen communication standard for multimedia applications in the home. Secondly, it is used to provide access to the home automation system from Wi-Fi enabled devices, as an alternative to the Zigbee based local controller. This approach was taken because

homes increasingly have Wi-Fi networks and Wi-Fi enabled devices such as PDA's and mobile phones. The additional cost of a Zigbee based controller in these situations is unwarranted. Also, the high data rate nature of Wi-Fi allows for greater flexibility in interface design. Wi-Fi implements the IEEE 802.11 standard and offers wireless networking through the use of radio frequency. There are different versions of this protocol. The dominant protocol in use today is IEEE 802.11g, which operates in the unlicensed 2.4 GHz band and provides a maximum raw data rate of 54 Mbps.

III. SYSTEM IMPLEMENTATION

A ZigBee based home automation system is implemented for the monitoring and control of household devices. To cater for the household's high data rate needs, such as multimedia entertainment, a Wi-Fi network is implemented. A home gateway has been developed to provide interoperability between these networks. The home gateway presents a unified interface for users to locally and remotely access home networks. The security and safety of the home automation network is realised through the development of the earlier described virtual home on the Home Gateway. To demonstrate the feasibility and effectiveness of the proposed system four devices, a light switch, radiator valve, safety sensor and ZigBee remote controller have been developed and integrated with the home automation system. This section provides a thorough discussion of the system implementation.

A. ZigBee Home Automation Network

The ZigBee home automation network consists of a coordinator, routers and several end devices. The coordinator is responsible for starting the ZigBee network. During the network initialisation phase, the coordinator scans the available radio channels to find the most suitable. Normally this will be the channel with the least activity, in order to reduce the level of interference. It is possible to limit the channels scanned, for example excluding those frequencies ranges used by the Wi-Fi network included in the proposed architecture. But, our experiments have shown that the average time taken to scan all the available channels is 9 seconds (to the nearest second). This scan time is relatively small and as the home coordinator is initialised infrequently this is an acceptable delay when contrasted with the performance increase possible through the use of a channel with less interference. The coordinator is preprogrammed with the PAN ID (Personal Area Network Identifier), although it is possible for the coordinator to dynamically scan for existing network PAN IDs in the same frequency and generate a PAN ID that does not conflict. All home devices connected to the ZigBee home automation network are assigned a fixed 64 bit MAC address. Additionally, each device is assigned a dynamic 16 bit short address that is fixed for the lifetime of the network. At this stage of the network initialisation, the coordinator assigns itself the short address 0x0000. After the coordinator's initialisation phase the coordinator enters "coordinator mode", during this phase it

awaits requests from ZigBee devices to join the network. The ZigBee devices developed for the home network, as mentioned, includes a light switch, radiator valve, safety sensor and ZigBee remote control. A ZigBee end node has been integrated with these devices. As the devices are started, during their respective initialisation stage, the node scans for available channels to identify the network it wishes to join. There may be multiple networks in the same channel, these networks are normally distinguished by their PAN ID. The node selects which network to join based on the PAN ID. The node sends a request to the network coordinator to join the network. The request is sent to the coordinator directly or through a neighbouring router on the desired network with which the node shares the best signal. On receipt of the request the coordinator judges whether the requesting device is permitted to connect to the home automation network. The standard implementation of most ZigBee networks prevents unauthorised devices joining the network by providing a short user defined period where device may join. This, in our opinion, does not on its own provide sufficient network security. To enhance the systems security the proposed system encrypts all device communications including the requests to join the home network with a private key. Only those devices that are in possession of the correct private key can successfully connect to the home network. The devices that are permitted to join the network are recorded in the device database and stored on the network coordinator. A partially connected mesh topology was adopted for the ZigBee home automation network. Due to the nature of the home environment where communication interference is constantly fluctuating, the advantage of increased communication routes available through the adoption of a mesh topology outweighs the added routing complexity.

B. Wi-Fi Network

The home's Wi-Fi network was implemented through a standard Wireless (802.11b and 802.11g) ADSL Modem Router, with a 4 port switch. The modem provides two primary functions. Firstly, the modem provides the connection between the Internet and local Wi-Fi network; hence extending access to the Wi-Fi enabled home gateway to any location with Internet access. Secondly, any local Wi-Fi enabled device within range of the home's Wi-Fi network can directly access the home gateway. This provides a low cost communication method with the home network, reduced infrastructure costs where Wi-Fi devices are already in use. Also, home owners can monitor and control the home automation network, using familiar technology and devices.

C. Home Gateway

A thorough review of existing home gateway technologies revealed that no off-the-shelf solution exists that provides the functionality specified in the requirements for the home gateway, as previously discussed. This included the provision of interoperability between the Internet, Wi-Fi and ZigBee networks. Hence, it was necessary to develop a bespoke home gateway. The home gateway consists of a Wi-Fi module, a ZigBee Microcontroller and a power supply.

The Wi-Fi module provides low cost and embedded serial to Wi-Fi connectivity. The ZigBee Microcontroller provides the connection to the ZigBee network. The Wi-Fi module connects to the home's local Wi-Fi network and the ZigBee microcontroller connects to the ZigBee home network as an end device. The home gateway once started enters the configuration stage. During the configuration stage the embedded Wi-Fi module establishes a connection with a local Wi-Fi network.

The parameters for the Wi-Fi connection such as network SSID and security parameters are preconfigured. Simultaneously, the ZigBee microcontroller searches for a ZigBee home network and, as discussed, establishes a connection. As with the Wi-Fi module, the ZigBee microcontroller's connection parameters are preconfigured. This concludes the configuration stage. Once the home gateway has been initialised, an idle state is entered until input is received. Input can originate from both the Wi-Fi network for input to the ZigBee network, or conversely from the ZigBee network for output to the Wi-Fi network. Input from the Wi-Fi network normally takes the form of commands from user interface devices. The input from the ZigBee network normally takes the form of responses to commands received earlier from user interface devices.

IV. EVALUATION

The implemented system was evaluated both quantitatively and qualitatively. To demonstrate the feasibility and effectiveness of the proposed system, four devices, a light switch, radiator valve, safety sensor and ZigBee remote control have been developed and integrated with the home automation system. These systems were subjected to a cycle of strenuous operations to simulate a high level of everyday usage. The light state was changed 20 times using the ZigBee remote control and 20 times using the Wi-Fi controller. Similarly the radiator valve state was changed 20 times using the ZigBee controller and 20 times using the Wi-Fi controller. The experiments showed the correct functionality of the devices 100% of the time.

But, the ZigBee controller had an average access delay of 670 ms while controlling the light switch, whereas the access delay incurred for controlling the radiator valve was small and subsequently could not be measured with our recording instruments. This implies that the majority of the access delay lies in the actuation of the light switch and subsequent bulb state change and is not attributable to the method of control. Taking this into account the access delay for the light bulb (1337 ms) can be adjusted by removing the 670 ms access delay attributed to the switch actuation to provide a more realistic access time for the Wi-Fi controller for the light switch of 667 ms. This average access delay is supported by the access delay recorded for the radiator valve of 613 ms. The viability of the home automation architecture was evaluated through real world testing of the proposed system with the developed radiator valve. The radiator valve was tested in a real house. The radiator valve was located in the test house's living room, on the ground floor. The radiators

existing TRV valve was replaced with the prototype automatic radiator valve. The local controller was put on a desk 2m away from the radiator and connected to a laptop. This configuration allowed test software running on the local controller to print out the desired temperature set by the user, current temperature around the radiator and time taken to reach the desired temperature by the automatic radiator valve.

V. CONCLUSION

This paper has reviewed the existing state of home automation systems, and identified and discussed five areas that have hindered consumer adoption of such technologies. Briefly, the areas include: the complexity and expense of the architectures adopted by existing systems, the intrusiveness of the system installations, the lack of interoperability between different home automation technologies, and the lack of interoperability between systems developed by different manufacturers that utilise the same technology. Interface inflexibility and the inconsistent approaches adopted towards security and safety are also problems. A novel architecture for a home automation system is proposed and implemented, using the relatively new communication technology ZigBee. The use of ZigBee communications technology helps lower the expense of the system and the intrusiveness of the respective system installation. The incorporation of the virtual home concept coordinates the systems security and safety efforts in a clear and consistent manner. The inclusion of a home gateway helps overcome the problems of network interoperability. The home gateway in our implementation provides interoperability between the local ZigBee and Wi-Fi networks and the Internet. Also the home gateway offers the potential to be easily extended to include interoperability for other communication standards. Furthermore, the home gateway unifies the interface offered by the system across the different networks and devices used to access the system. The feasibility and appropriateness of the proposed architecture and technologies in the creation of a low cost, flexible and secure system has been successfully evaluated both through experimentation and user trials. Experimentation has highlighted the stability of the novel architecture adopted, including the minimal impact of the inclusion of the virtual home on system's performance. The potential for successful co-existence and interoperability of Wi-Fi and ZigBee has been practically proven with implementation with a real home automation system. Focus group sessions have shown a positive attitude towards the developed system and significant support for the diverse modes of control, monitoring, and integration with existing home networks such as Wi-Fi.

REFERENCES

- [1] K. Bromley, M. Perry, and G. Webb. "Trends in Smart Home Systems, Connectivity and Services", www.nextwave.org.uk, 2003.
- [2] A. R. Al-Ali and M. Al-Rousan, "Java-based home automation system", *IEEE Transactions on Consumer Electronics*, vol. 50, no. 2, pp. 498-504, 2004.
- [3] N. Sriskanthan, F. Tan and A. Karande, "Bluetooth based home

- automation system", *Microprocessors and Microsystems*, Vol. 26, no. 6, pp. 281-289, 2002.
- [4] H. Ardam and I. Coskun, "A remote controller for home and office appliances by telephone", *IEEE Transactions on Consumer Electronics*, vol. 44, no. 4, pp. 1291-1297, 1998.
- [5] T. Baudel and M. Beaudouin-Lafon, "Charade: remote control of objects using free-hand gestures", *Communications of the ACM*, vol. 36, no. 7, pp. 28-35, 1993.
- [6] T. Saito, I. Tomoda, Y. Takabatake, J. Ami and K. Teramoto, "Home Gateway Architecture And Its Implementation", *IEEE International Conference on Consumer Electronics*, pp. 194-195, 2000.
- [7] N. Kushiro, S. Suzuki, M. Nakata, H. Takahara and M. Inoue, "Integrated home gateway controller for home energy management system", *IEEE International Conference on Consumer Electronics*, pp. 386-387, 2003.
- [8] S. Ok and H. Park, "Implementation of initial provisioning function for home gateway based on open service gateway initiative platform", *The 8th International Conference on Advanced Communication Technology*, pp. 1517-1520, 2006.
- [9] D. Yoon, D. Bae, H. Ko and H. Kim, "Implementation of Home Gateway and GUI for Control the Home Appliance", *The 9th International Conference on Advanced Communication Technology*, pp. 1583-1586, 2007.
- [10] K. Shuaib, M. Boulmalf, F. Sallabi and A. Lakas, "Co-existence of Zigbee and WLAN - a performance study", *IFIP International Conference on Wireless and Optical Communications Networks*, pp. 5, 2006.
- [11] Jennic, "JN-AN-1059 Deployment guidelines for IEEE 802.15.4/ZigBee wireless networks", 37-38, 2007.